

STRIKER® 3000

THE BENCHMARK IN ARFF RESPONSE.

The Oshkosh® Striker 3000 is custom engineered to offer the ultimate in fast emergency response, charging from 0 to 50 mph (80 km/h) within 35 seconds. The sleek aerodynamic styling tells you immediately this is no ordinary ARFF truck, but a revolutionary new concept in airport emergency response.

The Striker 3000 combines unchallenged mobility with a smooth, stable ride and easy operation. The custom cab delivers driver comfort and outstanding visibility. And all systems are designed to support the highest levels of efficiency and safety for the response team.

Oshkosh Corporation has shaped the technology of modern ARFF trucks for more than four t. With the Striker, Oshkosh again sets the industry standard for performance.

EXTREME MOBILITY. Your response doesn't stop where the runway ends. With all-wheel drive and Oshkosh TAK-4® independent suspension as standard features, the Striker can outmaneuver and outperform any ARFF vehicle in its class on and off the runway. The unique independent suspension system reduces stopping distance and helps tires hug the pavement for enhanced cornering and handling. An optional rear steer system provides even more maneuverability. Ground clearance is a full 17 inches (43.2 cm).

ROCK SOLID STABILITY.

The Striker features a wide track and low center of gravity to provide exceptional static side-slope stability of at least 30°. Independent suspension and optional central tire inflation also enhance stability while maneuvering.

UNMATCHED VISIBILITY. The Striker provides unobstructed panoramic views of the scene with excellent forward, upward and lateral visibility. The cab features almost 80 sq. ft. of glass.



PREMIUM RIDE QUALITY. No other ARFF vehicle can offer the ultra-smooth ride delivered by Oshkosh's patented independent suspension system. Enjoy more than 16 inches (40.6 cm) of wheel travel. And, more than 80,000 hours of testing make this system one more example of tough, Oshkosh reliability.

SPACIOUS, COMFORTABLE AND FIREFIGHTER FRIENDLY. This revolutionary cab was designed with firefighters' comfort and convenience in mind. It offers best-in-class interior space to comfortably seat up to five. Each seat features integral 3-point seat belts. The wrap-around, cockpit style instrument panel puts controls

within easy reach of driver and crew. Controls are grouped by function for quicker access during an emergency. The cab accommodates

various cameras and systems. A high capacity heating and cooling system generates a full 60,000 Btu to ensure a comfortable interior temperature.



SUPERIOR FIRE POWER. For the confidence of unparalleled fire attack capability, the Striker 3000 can be equipped with both a dry chemical system (500 lb/225 kg) and Halotron™ I system (460 lb/207 kg), each with its own hosereel. A High Reach Extendable Turret (HRET) and high volume bumper turrets are also available. A 3,000 gallon (11356 l) water tank, 420 gallon (1590 l) foam tank, 1,200 gpm (4542 lpm) roof turret and 300 gpm (1136 lpm) bumper turret are standard.

EASY MAINTENANCE. Preventative maintenance is quick and easy with single point access for lubrication fills, air tank drains, and electrical connections including circuit breaker box. Parts commonality between models is an added benefit when you upgrade your fleet to the new Striker Series from Oshkosh. And, you'll have the added confidence of knowing your vehicles are supported by expert Oshkosh technicians.



ONLY ONE ARFF TRUCK OUTPERFORMS EVERYTHING ELSE IN ITS CLASS: THE OSHKOSH STRIKER.

TYPICAL SPECIFICATIONS

PERFORMANCE:

- **Acceleration**^{1,2}: 0 to 50 mph (80 km/h) in 35 seconds
- **Top Speed**¹: 70 mph (112 km/h)
- **Side Slope Stability (Static)**: >30°
- **Gradeability**²: Ascend/descend a 50% grade
- **Vehicle Clearance Circle**: 117 ft. (35.6 m)
- **Dimensions**: 475 in. (1206.5 cm) length; 122 in. (310 cm) width (excluding rear view mirrors); 136 in. (345.4 cm) height without HRET; 150 in. (381 cm) with HRET

CHASSIS:

- **Anti-Lock Braking System (ABS)**
- **Cab**: Aluminum construction; seating for up to five; center steering position; wrap-around, cockpit style instrument panel; easy to read backlit gauges and controls
- **Engine**: Caterpillar C-16 diesel; four cycle; in-line six; 680 bhp (506 Kw) minimum at 2,100 rpm with a peak torque of 1,950 ft. lbs. @ 1,400 rpm
- **Transmission**: Allison 4800 EVS; electronic; 7-speed; automatic
- **Transfer Case**: Oshkosh; independently mounted; with torque proportioning differential and driver selected locking mechanism
- **Front Axle**: 29,000 lb. (13152 kg); Oshkosh double reduction with bevel gear differential; driver operated differential lock
- **Front Brakes**: Dual wedge type
- **Rear Axles**: 2 x 29,000 lb. (13152 kg) 58,000 lb. (26304 kg); Oshkosh double reduction with bevel gear differential; driver operated differential lock
- **Rear Brakes**: S-cam type; air/mechanical spring actuation
- **Suspension**: Oshkosh TAK-4 independent system with dual control arms and single coil spring; up to 16 in. (40.6 cm) of wheel end travel; provides superior all-terrain mobility, improved

ride quality and improved handling

- **Tires**: Michelin® 24R21 XZL
- **GVWR**: 87,000 lb. (39456 kg)
- **Wheelbase**: 236 in. (599.5 cm)

FIREFIGHTING SYSTEM:

- **Roof Turret**: Non-aspirating; electric joystick control; 600/1,200 gpm (2271/4542 lpm)
- **Bumper Turret**: Non-aspirating; electric joystick control; 300 gpm (1136 lpm)
- **Handlines (Foam/Water)**: Two preconnect type (one each side) with 150 ft. (46 m) of 1.75 in. (44 mm) ID hose and a 125 gpm (473 lpm) pistol-grip nozzle
- **Water Tank**: 3,000 gallon (11356 l) capacity; constructed of corrosion and UV resistant polypropylene
- **Foam Tank**: 420 gallon (1590 l) capacity; constructed of corrosion and UV resistant polypropylene
- **Fire Pump**: Power divider driven Waterous CRQA; single stage centrifugal; cast iron body; brass impeller; stainless steel shaft; pump-and-roll capable; 1,950 gpm (7381 lpm) at 240 psi (1657 kPa)
- **Foam Proportioning System**: Around-the-pump

POPULAR OPTIONS:

This is a partial listing of major options. Additional and special request options are also available.

- Disc brakes (outboard mounted)
- Mechanical rear axle steering
- Central tire inflation
- Air conditioning
- Winterization system to -40° F/C
- Hydraulic generator
- Auxiliary lighting
- High Reach Extendable Turret (HRET)
- High volume, fixed mount or low attack bumper turrets; 1,200 gpm (4542 lpm) capacity
- Dry chemical system with single agent or dual agent handline, and/or primary turret discharge capability

- Hydro-Chem™ direct injection, dry chemical nozzle for primary turret and/or dual agent handline discharge
- Halotron I system with single agent or dual agent handline, and/or HRET discharge capability
- Electronic Foam Proportioning

The Striker 3000 meets or exceeds all National Fire Protection Association (NFPA) 414, Federal Aviation Administration (FAA) and International Civil Aviation Organization (ICAO) requirements for 3,000 gallon water capacity ARFF vehicles.

For reference only. Specifications, descriptions, and illustrations in this literature are as accurate as known at the time of publication but are subject to change without notice. Ratings are general guidelines. Actual ratings may vary with application and duty cycle. Illustrations may include optional equipment and accessories but may not include all standard equipment. Specifications are subject to change without notice. Consult Oshkosh Corporation for additional information.

©Oshkosh Corporation, Oshkosh, Striker, TAK-4 and the Oshkosh logo are registered trademarks of Oshkosh Corporation, Oshkosh, WI

Halotron I is a trademark of Halotron, Incorporated, Las Vegas, NV

Michelin is a registered trademark of Michelin Tire Corporation, Greenville, SC

All measurements are nominal values.

Printed in U.S.A.

Striker 3000-S 8-09

¹ On dry, level pavement

² Based on 87,000 lb (39456 kg) gross vehicle weight



OSHKOSH CORPORATION

2307 Oregon Street
P.O. Box 2566
Oshkosh, Wisconsin 54903-2566 USA
920/235-9150
www.oshkoshcorporation.com